

RIEZLER

Control unit

MSE-100

Article-No. 5-0036-001



Technical data

| | |
|-------------------------------------|--|
| Features | High-definition, daylight-suitable TFT display, integrated video recorder, integrated meter counter, Li-Ion battery pack |
| Screen size | 5.6 inch |
| Resolution | 640 x 480 |
| Pan and tilt camera controls | with optional remote control |
| Crawler controls | ✘ |
| Storage | SD card (up to 32 GB) |
| Video format | MPEG-4 with single frame function |
| Software | ✘ |
| Sensor data overlay | pan and tilt angle in degrees, internal pressure in bar (alarm function when threshold is exceeded) |
| Battery | Li-Ion battery with a battery charger and charge indicator |
| Power supply | 12 - 24 V DC via external power supply (100 - 240 V AC), 12 V jack for car operation |
| Microphone jack for voice recording | ✓ |
| Interfaces | 1 x BNC Video-IN, 1 x BNC Video-OUT |
| IP protection class | IP 54 |
| Operating temperature | 0° to 40° C 32° to 104° F |
| Storage temperature | 0° to 40° C 32° to 104° F |
| Material | plastic / aluminium |
| Dimensions (L x W x H) | 270 x 120 x 245 mm 10.7 x 4.7 x 9.7 in |
| Weight | ca. 2.4 kg 5.3 lbs |

RIEZLER Inspektionssysteme GmbH & Co. KG

Sportplatzweg 5 | 87471 Durach | Germany
Tel. +49 (831) 27714 | info@riezler.eu | www.riezler.eu