

# RIEZLER

## Control unit

### MSE-400

Article-No. 5-0040-001



## Technical data

Features	High-definition, daylight-suitable touchscreen TFT display, powerful industrial PC, inspection software, Li-Ion battery pack
Screen size	10 inch
Resolution	1024 x 768
Pan and tilt camera controls	✓
Crawler controls	✗
Storage	internal SSD hard disk (256 GB)
Video format	MPEG-4 with single frame function
Software	RiVision
Sensor data overlay	pan and tilt angle in degrees, internal pressure in bar (alarm function when threshold is exceeded)
Battery	2 Li-Ion battery with a battery charger and charge indicator
Power supply	12 - 24 V DC via external power supply (100 - 240 V AC), 12 V jack for car operation
Microphone jack for voice recording	✗
Interfaces	2 x USB 3.0, 1 x RJ45, 1 x Video-IN, 1 x Video-OUT
IP protection class	IP 22
Operating temperature	0° to 40° C   32° to 104° F
Storage temperature	0° to 40° C   32° to 104° F
Material	plastic / aluminium
Dimensions (L x W x H)	350 x 180 x 315 mm   13.8 x 7.1 x 12.4 in
Weight	ca. 5.5 kg   12.1 lbs

**RIEZLER Inspektionssysteme GmbH & Co. KG**

Sportplatzweg 5 | 87471 Durach | Germany  
Tel. +49 (831) 27714 | [info@riezler.eu](mailto:info@riezler.eu) | [www.riezler.eu](http://www.riezler.eu)